

RE: 26' – 12 Bunk Tag Trailer w/Galley, Bathroom & Shower

Mohawk Ltd. is pleased to provide the following preliminary specifications and pricing for a **26' Bunk Trailer** per the attached drawings and the following specifications:

- Rollingstar RS826TS60 26' x 102" Custom Enclosed Trailer: 14,000 lb. GVWR, smooth FRP fiberglass insulated wall system, structural aluminum trailer frame, tandem torsion electric brake axle suspension, radial tires on machined aluminum modular wheels, 2-5/16" adjustable height ball coupler w/7,000 lb. drop-leg jack & welded safety chains, one piece aluminum roof, D.O.T. compliant lighting
- Aluminum trailer frame
- Insulated FRP composite walls, 1" R-7 urethane foam insulation. 1/4 panels, 1-1/2 total wall thickness
- (2) 30" x 80" RV style door w/knob and dead bolt style locksets
- Heavy duty pull-out steps below front personnel door, built-in ladder type steps in skirting of rear door
- (4) window, 30"x15" tinted, Hehr 5900 Series
- Mini blinds for above windows, RV style
- Aluminum "Alcoa" wheels for 235 tires set of (4)
- Spare tire w/mount 235/85 (standard on white mod rim)
- Crankdown leveling jacks all 4 corners, removable for storage inside trailer
- Deluxe ceiling package includes 6" fiberglass insulation, white poly-board ceiling liner
- Carpeted interior walls
- PVC commercial flooring (ribbed or coin pattern)
- Floor insulation, blown in-place polyurethane foam R-11
- Bathroom: partitions w/1 ea. 24" hinged bathroom door with lockset, walls are poly-board or FRP board
- Partition w/pocket door, built up w/white FRP paneling
- (2) 12v "Polar" powered roof vent (thermostatically controlled with rain sensor, automatic or manually controlled) (bathroom and shower areas) w/"MaxAir" roof vent cover
- (6) 12 volt dome light (white lens) w/wall switches
- (2) 12 volt 26 degree down trapazoidal surface mount area light, Code 3, individually switched
- (2) 12 volt accessory power receptacle
- Generator enclosure, front tongue mounted, approx. 60"Wx27"Hx27"D, aluminum ATP construction w/SS locking latch and gasket
- 7.5 kW Onan "Quiet Diesel" Generator (60A) mounted in front generator compartment with 50 gallon frame mounted fuel tank, battery, auto transfer switch and remote start /stop switch
- Fuel gauge & sending unit for certified fuel tank mounted inside trailer
- Rapid-fill fuel filler w/locking access door
- Magnetek Model 100D 220V/110V/12V 50 amp entrance/distribution panel
- 50-amp 120-240 volt shore power w/25' shore cord and exterior power receptacle
- (4) 48" fluorescent ceiling light, T-8 type w/electronic ballasts, flush mount 2-bulb, 110 volt w/(2) 3-way wall switches
- (3) round fluorescent light fixture, surface mount (bathroom/galley/shower), individually switched
- (6) 110V duplex interior power receptacles (stand alone-surface mount)
- (4) 110v GFCI protected duplex power outlets, exterior w/weatherproof cover
- (2) 500W 110 volt flush mount quartz scene lights (4.2A), individually switched
- (2) radio coax jack, includes 50 ohm (RG58AU or equivalent) coax cable connected to (1) roof mounted screw-on antenna base
- (2) 13.5 BTU roof mount air conditioner, Coleman (15A), w/5600 BTU heat strip, ducted (vents with shutoffs), vent locations to be determined
- Battery operated smoke alarm
- Battery operated CO detector
- Fire extinguisher, 5 lb.
- Microwave oven: Dometic CDMW10MW 1.1 cu.ft. capacity, 1000 watt

800-225-6642

Mohawk Ltd.

A WBE and ISO 9001:2000 Certified Company

- Refrigerator, Dometic RM2193 1.94 cu.ft. AC/DC/Propane built-in, includes exterior vent/access door (20-7/8"Hx17-3/4"Wx21"D) (1.2 amps AC)
- 170 gallon frame mounted potable water tank w/drain (stainless steel)
- 170-gallon frame mounted grey water tank w/drain (stainless steel)
- 12V electric demand water pump with accumulator, includes potable & waste water tank level gauges, **propane tank level gauge** and system monitoring panel
- Auto dump switches and valves for grey water and black water tanks
- Tankless on-demand hot water heater
- 19 gallon fixed frame mounted LP tank, regulator for on-demand hot water heater
- Exterior city water hookup
- RV type toilet w/ 85 gallon waste holding tank and appropriate drain valves, fittings and sewage hose
- Shower enclosure w/fixture and low-flow shower head, includes shower door

Cabinets and Work Surfaces

Storage cabinets and work surfaces are located per attached drawing. Cabinets feature locking "T" handles and 1-5 shelves (depending on cabinet height). Cabinet casework and doors feature plastic laminate construction over *plywood* cores with radius corners and impact resistant edge reinforcement. Work surfaces are "NevaMar" abrasion resistant plastic laminate over *plywood core* construction. Front edge of work surfaces is radiused impact resistant edge banding.

- (4) 21"Wx32"D x full height tower unit to provide end support and storage for each bunk, includes 1/2" sliding doors w/aluminum track at each bunk level
- (12) heavy duty bunk frame w/1-1/8"x6 rails, 2"x2" aluminum angle supports to walls and 3/4" plywood mattress support
- (12) 30"x75"x5" thick KingKoil foam mattress
- 24"Wx24"D full height closet cabinet w/shelves
- Galley, approx. 70"W includes full length countertop w/stainless steel sink and faucet, overhead cabinets with shelves and microwave cabinet, base cabinets w/(4) drawers

800-225-6642

PO Box 340 • One Newell Lane • Chadwicks, NY 13319 • Fax: 315-737-7347
www.mohawkLtd.com • E-mail - info@mohawkLtd.com



Generator Enclosure
w/Onan 7.5 kW "Quiet Diesel"
Generator

